



NOTES: UNLESS OTHERWISE SPECIFIED
 1. ALL RESISTOR VALUES ARE IN OHMS
 2. ALL CAPACITOR VALUES ARE IN MICROFARADS
 3. ALL CAPACITORS ARE NORMALLY OPEN
 4. 20 AND 50 ARE 20MFD AND 50MFD
 5. 0.1, 0.15, AND 0.15 ARE 0.15, 0.15, AND 0.15
 6. A SYMBOL INDICATES FACTORY SET

STATIC DC VOLTAGES ADDED 20-10-69 J.E.P.
 EFFECTIVE FOR \$/N SUFFIX K

REV. 2. 200 6/27/69 (REV. 1/17/69)
 REV. 1. 200 6/27/69 (REV. 1/17/69)
 REV. 0. 200 6/27/69 (REV. 1/17/69)
 REV. 0. 200 6/27/69 (REV. 1/17/69)
 REV. 0. 200 6/27/69 (REV. 1/17/69)
 REV. 0. 200 6/27/69 (REV. 1/17/69)
 REV. 0. 200 6/27/69 (REV. 1/17/69)

UNITED SOLID STATE ELECTRONICS	15133 (19) 197
INDUSTRIES	15133 (19) 197
10000 10000	15133 (19) 197
10000 10000	15133 (19) 197

REV. 1. 200 6/27/69 (REV. 1/17/69)
 REV. 0. 200 6/27/69 (REV. 1/17/69)
 REV. 0. 200 6/27/69 (REV. 1/17/69)
 REV. 0. 200 6/27/69 (REV. 1/17/69)
 REV. 0. 200 6/27/69 (REV. 1/17/69)